



Wide Band Variable Gain Low Noise Amplifier 27GHz~32GHz

Features

- Gain: 36dB Typical
- Noise Figure: 2.0dB Typical
- Output P1dB : +22dBm Typical
- PSAT Output Power: 24dBm
- Supply Voltage: +12V

Typical Applications

- Wireless Infrastructure
- Military & Aerospace
- Test and Measurement

Electrical Specifications, TA = +25 °C, Vcc = +12V, Vctl= -4.5V

Parameter	Min.	Typ.	Max.	Min.	Typ.	Max.	Units
Frequency Range	27		29	29		32	GHz
Gain		36			36		dB
Gain Adjustable Range		13			16		dB
Gain Flatness		±2.0			±2.0		dB
Gain Variation Over Temperature (-45°C ~ +85°C)		±1.0			±1.0		dB
Noise Figure		2.2			2.2		dB
Input VSWR		1.6			2.0		: 1
Output VSWR		1.8			1.8		: 1
Output 1dB Compression Point (P1dB)	18	22		18	22		dBm
Saturated Output Power (Psat)		24			24		dBm
Output Third Order Intercept (OIP3)		28			30		dBm
Isolation S12		-60			-60		dB
Supply Current (Vcc=+12V, Vctl=-4.5V to -1V)		160	200		160	200	mA
Weight	/						Ounces
Impedance	50						Ohms
Input / Output Connectors	2.92 - Female						
Finish	Standard: Gold 40 micron; Nickel 220 micron thickness						
	Option: Gold 80 micron; Nickel 180 micron thickness						
Material	Aluminum						
Package Sealing	Epoxy Sealed (Standard)						
	Hermetically Sealed (Optional)						

Wide Band Variable Gain Low Noise Amplifier 27GHz~32GHz



Absolute Maximum Ratings

Operating Voltage	+15V
Vg Control Voltage	-4.5V to -1V
RF Input Power (@25°C, 50Ω)	-20dBm

Biasing Up Procedure

Step 1	Connect Ground Pin
Step 2	Connect input and output
Step 3	Connect +12V biasing
Step 4	Connect Vctl Control
Step 5	Turn on +12V biasing
Step 6	Turn on Vctl Control
Power OFF Procedure	
Step 1	Turn off Vctl Control
Step 2	Turn off +12V biasing
Step 3	Remove RF connection
Step 4	Remove Ground.

Environmental Specifications and Test Standards


Parameter	Standard	Description
Operational Temperature	MIL-STD-39016	-45°C~+85°C
Storage Temperature		-50°C~+125°C
Thermal Shock		1 Hour@ -45°C → 1 Hour @ +85°C (5 Cycles)
Random Vibration		Acceleration Spectral Density 6 (m/s) Total 92.6 RMS
Electrical & Temperature Burn In		Temperature +85°C for 72 Hours
Shock		1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude		Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883	MIL-STD-883 (For Hermetically Sealed Units)

Wide Band Variable Gain Low Noise Amplifier 27GHz~32GHz



Outline Drawing:

All Dimensions in mm [inches]



Heat Sink required during operation (Sold Separately)

Ordering Information

Part No.	ECCN	Description
RAGC2732GA	EAR99	27-32GHz Wide Band Variable Gain Low Noise Amplifier

Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

Wide Band Variable Gain Low Noise Amplifier 27GHz~32GHz