

Absorptive Digital Control Attenuator 0-18GHz



Note: Photo is for illustration purposes only.
Please refer to outline drawing.

Product Description

RFDAT0018G1C is an absorptive digital control attenuator with a frequency range of 0 to 18GHz.

The maximum power input of this attenuation is 30dBm. The insertion loss is 2.5dB with a typical attenuation range of 31.5dB.

The working temperature of this product is between - 40°C and + 85°C.

Features

- Absorptive Digital Control Attenuator
- Att.Range:31.5dB
- Single Positive Control Line Per Bit

Typical Applications

- Wireless Infrastructure
- Military and Aerospace Applications
- Test Instrumentation
- Radar Systems
- 5G Wireless Communications
- Microwave Radio Systems
- TR Modules
- Research and Development
- Cellular Base Stations

Electrical Specifications (T_A=+25°C) ,Vdd = +5V, TTL = 0 / +5V

Parameter	Min	Typ	Max	Units
Frequency Range		0-18		GHz
Attenuation Range		31.5		dB
Attenuation Flatness: (Referenced to Insertion Loss)		±1.0		dB
Control Bits		1		Bit
Control Step Size		31.5		dB
Insertion Loss		2.5		dB
Insertion Loss Temperature Coefficient		0.003		dB/ °C
Input VSWR (All Atten. States)		1.5		: 1
Output VSWR (All Atten. States)		1.5		: 1
Input 1dB Compression Point (P1dB)		27		dBm
IP3 Input		43		dBm
Switching Speed		200Typ.		ns
Bias Current (+5V)		20Typ.		mA
Weight		/		lbs.
Impedance		50		Ohms
Input / Output Connectors	SMA-Female (Input) – SMA-Female (Output)			
Interface and Control Connector	MICRO-D9 (Female)			
Package	Epoxy Sealed (Standard)			
	Hermetically Sealed (Optional)			

Absolute Maximum Ratings


Parameter	Rating
Biasing Voltage	+5V±10%
RF Input Power	+30dBm

Environmental Specifications and Test Standards

Parameter	Description
Operational Temperature	-40°C to +85°C (Case Temperature)
Storage Temperature	-50°C to +105°C
Thermal Shock	-40°C → +85°C (5 Cycles / 10 hours)
*Random Vibration	MIL-STD-202G Table 214-I, Test Condition Letter C 1.5 Hours Per Axis
High Temperature Burn In	Temperature +85°C for 72 Hours
Shock	1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883 (For Hermetically Sealed Units)

*For vibration testing details please see additional information section.

Outline Drawing



Additional Information

Documentation	Webpage
ESD Policy	https://rflambda.com/pdf/rflambda_esd_control.pdf
Connector Torque Specifications	https://www.rflambda.com/pdf/Torque_Specifications.pdf
Random Vibration Test Standard	https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf

Ordering Information

Part Number	Modification	Description
RFDAT0018G1C	Standard	0-18GHz Digital Control Attenuator

Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.